



1 - PWR. OFF  
 2 - HIGH  
 3 - MEDIUM  
 4 - LOW

PWR OFF-TONE

PHONES

PM

LS1

PITCH CONTROL  
 LI1

**NOTES**

1. RESISTOR VALUES ARE IN OHMS UNLESS OTHERWISE SPECIFIED.
2. CAPACITOR VALUES ARE IN MMF. UNLESS OTHERWISE SPECIFIED.
3. RESISTOR RATINGS ARE 1/2 WATT UNLESS OTHERWISE SPECIFIED.

VALUES AND TOLERANCES SHOWN ARE NOMINAL AND VARIATIONS MAY BE FOUND. IT IS RECOMMENDED THAT THE VALUE OF ANY REPLACEMENT CORRESPOND TO THE NOMINAL VALUE OF THE PART BEING REPLACED.

\* SOME UNITS WILL HAVE A 12,000 OHM, 4 WATT, W/W RESISTOR REPLACING R-10 & R-69.

LAST R SYMBOL R-69  
 LAST C SYMBOL C-64

SWITCH S4B SHOWN IN POSITION 1.  
 SWITCH IS CLOSED IN POSITIONS 2, 3 & 4.



REPRESENTS COILS L1 TO L10

Hallicrafters S-85, S-85U