



VI, V2, V3 - 12AX7
 S1 - 5 POS. 4 SECT. SELECTOR SWITCH
 S2 - POWER SWITCH (PART OF GAIN CONTROL)
 S3 - CONSTANT AMPLITUDE CARTRIDGE SWITCH (PART OF LOAD CONTROL)

UNLESS STATED OTHERWISE, COMPONENT VALUES ARE AS FOLLOWS:
 RESISTANCE IN OHMS, K = X 1000,
 M = X 1,000,000
 CAPACITY LESS THAN UNITY IN MF,
 FILTER CAPACITY IN MF,
 CAPACITY GREATER THAN UNITY IN MMF

NOTE - C8 IS SUPPLIED WITH A 6 FOOT CABLE (PART J-121) TO OPERATE WITH AND BE POWERED BY A MCINTOSH POWER AMPLIFIER. PINS 5 AND 6 ON THIS CABLE ARE NOT CONNECTED.

C8 - P IS SUPPLIED WITH THE D-8 POWER SUPPLY. THE NECESSARY POWER CABLE IS A PART OF THE D-8.

REVISIONS		DATE	BY	SCALE	MATERIAL
1		12-20-56	J.W.		
2					
3					
4					
5					

McINTOSH LABORATORY, INC.
 320 Water St., Binghamton, N.Y.
 D-8A POWER SUPPLY
 DRAWN BY: J.W.C.
 DATE: 9-26-56
 DRAWING NO.: D-8A-1
 TRACED: SAE

SERIAL NO. 10600 AND UP