



ALL VOLTAGES MEASURED UNDER FOLLOWING CONDITIONS:  
 1 - USE OF 11 MEGOHMS INPUT IMPEDANCE VTVM VOLTMETER.  
 2 - ALL VOLTAGES ± 10% WITH RESPECT TO GROUND.  
 3 - A.C. INPUT AT 117 V 50-60 CPS.  
 4 - NO SIGNAL AT ANTENNA AND OTHER INPUT TERMINALS.  
 5 - FRONT PANEL CONTROLS AT:  
 MODE SELECTOR - MONO.  
 VOLUME CONTROL - MAX.  
 MUTING - OFF

UNLESS OTHERWISE SPECIFIED  
 ALL RESISTORS 1/2 W 20%  
 ALL CAPACITORS IN PF  
 ALL INDUCTORS IN MICRO H  
 FM. IF: 10.7 MC

SYMBOL NUMBERS NOT USED  
 R 80 C 28  
 R 87 C 33  
 C 35

FOR SERIAL NUMBERS 22T04 AND ABOVE

MATERIAL	TITLE	PART NO.
	SCHEMATIC, MR 67	
FINISH	McIntosh LABORATORY INC.	USED ON:
	2 Chambers St. Binghamton, N. Y.	
TOLERANCES - unless otherwise specified	SCALE	DATE
± 1% Resistors ± 5% Transformers	1/8"	1, 4, 65
± .005 Capacitors	1/4"	APR 54
	APP. 37	REV
		SC123-176