



NOTES:

- ALL RESISTANCE IN OHMS, 1/2 WATT AND ±20% TOLERANCE UNLESS OTHERWISE STATED. K=1,000, M=MEG OHM
- ALL CAPACITANCE IN MICROMICROFARADS, 100 VOLTS MIN. AND ±20% TOLERANCE UNLESS OTHERWISE STATED. GMV=GUARANTEED MIN. VALUE.
- TUNING RANGE FROM 540KC TO 1600KC
- I.F. FREQUENCY 262.5KC
- VOLTAGE MEASUREMENTS:
 1. ALL DC VOLTAGES MEASURED WITH A 20,000 OHM/VOLT METER, NO SIGNAL INPUT.
 2. ALL AC VOLTAGES MEASURED WITH AN AC V.T.V.M., AT FULL VOLUME, 1WATT OUTPUT.
 3. ALL VOLTAGES MEASURED WITH RESPECT TO CHASSIS.
 4. ALL VOLTAGES MEASURED WITH +7.2 VOLTS INPUT WITH NEGATIVE TERMINAL GROUNDED.

NO UNGROUNDED AC POWERED TEST EQUIPMENT SHOULD EVER BE USED.

DUMMY ANTENNA:

30UF SERIES AND 20UF SHUNT AT ANTENNA SOCKET, 0.1UF SERIES TO TRANSISTOR BASE ELEMENTS FOR GAIN MEASUREMENTS.

Volkswagen RO BT, RO BV
made by Bendix Aviation Corp.

